

## Portable Wireless PA System CWR-1060W

**Dual-Channel Wireless Ultra-Portable PA Amplifier – CWR-1060W**, is the ideal public address solution for small group of audience up 300 people. It can be used in a variety of applications and to extend PA coverage for voice and audio amplification.

- 70W max power output
- One-touch wireless frequency sync
- Bluetooth MP3 player with USB/TF
- Built-in UHF 16 Frequency Receiver
- Voice priority function
- ON/OFF Power switch to save power
- Come with battery and charging indicator
- Built-in Lithium Rechargeable Battery



Front View



Rear View

## Specifications

A) PA System	
Power Output	50W - 70W(max)
Speaker	Built-In 6" Full Range Speaker
Frequency Response	50Hz-18Khz ±3dB
Audio Input - Wired Mic	2 X MIC (1/4")
Audio Input - Line-in	1 X Line In (3.5mm), 2 X RCA
Line Output	2 X RCA
Voice Priority	Yes
Power Supply AC	15V 1.5A Power Adaptor
Power Supply DC & Battery	11.8V 4.4A Rechargeable Lithium battery
Recharging Time	9 ~ 10 Hours
Operating Time (depends on usage)	8 ~ 10 Hours
Battery Indicator	Battery level with charging status
Dimensions	200 (L) x 230 (W) x 340 (H) mm
B) Wireless Receiver	
Wireless Microphone - Option 1	Model : CW5-H Handheld microphone x 2
Wireless Microphone - Option 2	Model : CW5-BC Lavalier mic with bodypack transmitter x 2
Wireless Receiver Module	Dual Channel
Frequency Channel	UHF16 Frequency
Oscillation Mode	PLL Synthesized
Frequency Range	UHF 640 to 680 MHz
Receiving Sensitivity	-95dB
Spurious Emission	< 55dB
SNR Rate	> 95dB
Indicator	LED RF Signal
Wireless Mic RF Output Power	10mW



**CW5-H**  
Handheld microphone



**CW5-B**  
Bodypack transmitter