

Ultra Portable Wireless PA System

CWR-1052W

Ultra-Portable Wireless PA Amplifier – CWR-1052W, is the ideal public address solution for small group of audience up 150 people. It can be used in a variety of applications and to extend PA coverage for voice and audio amplification.

- 55W max power output
- Lightweight at 1.8 kg (Including battery)
- Carry handle and shoulder strap included for easy transportation
- One-touch wireless frequency sync
- ON/OFF Power switch to save power
- Come with battery and charging indicator
- Built-in Lithium Rechargeable Battery



Front View



Rear View

Specifications

A) PA System	
Power Output	35W - 55W(max)
Speaker	Built-In 5" Full Range Speaker
Frequency Response	50Hz-18Khz ±3dB
Audio Input - Wired Mic	1 X MIC (1/4")
Audio Input - Line-in	1 X Line In (3.5mm)
Line Output	1 X Line Out (3.5mm)
Power Supply AC	15V 1.5A Power Adaptor
Power Supply DC & Battery	11.8V 2200Mha Rechargeable Lithium Battery
Recharging Time	5 ~ 7 Hours
Operating Time (depends on usage)	6 ~ 10 Hours
Battery Indicator	Power LED, Charging/Low power LED
Dimensions	185 (L) x 90 (W) x 223 (H) mm
Weight	1.8 kg (includes battery)
B) Wireless Receiver	
Wireless Microphone - Option 1	Model : CW5-H Handheld microphone x 2
Wireless Microphone - Option 2	Model : CW5-BC Lavalier mic with bodypack transmitter x 2
Wireless Receiver Module	Dual Channel
Frequency Channel	UHF16 Frequency
Oscillation Mode	PLL Synthesized
Frequency Range	UHF 640 to 680 MHz
Receiving Sensitivity	-95dB
Spurious Emission	< 55dB
SNR Rate	> 95dB
Indicator	LED RF Signal
Wireless Mic RF Output Power	10mW



CW5-H
Handheld microphone



CW5-B
Bodypack transmitter